

ELB - LED Linear Fixtures

Specifications

4' linear fixtures for suspended mount applications

Architectural Styling – All Aluminum

DLC QUALIFIED PRODUCTS



Product Summary:

| | | |
|---|--|--|
| <p>Model #: ELB/LED-LR-48-30-830-TL4-MV ELB/LED-LR-48-30-835-TL4-MV ELB/LED-LR-48-30-840-TL4-MV ELB/LED-LR-48-30-850-TL4-MV</p> <p>Performance: Lumens = 3139 lm @ 3000k Lumens = 3260 lm @ 3500k Lumens = 3340 lm @ 4000k Lumens = 3420 lm @ 5000k</p> <p>Wattage = 28.7W >109.3 lm/W 120 – 277VAC</p> | <p>Model #: ELB/LED-LF-48-30-830-FP4-MV ELB/LED-LF-48-30-835-FP4-MV ELB/LED-LF-48-30-840-FP4-MV ELB/LED-LF-48-30-850-FP4-MV</p> <p>Performance: Lumens = 3193 lm @ 3000k Lumens = 3235 lm @ 3500k Lumens = 3340 lm @ 4000k Lumens = 3460 lm @ 5000k</p> <p>Wattage = 29.4W > 108.5 lm/W 120 – 277VAC</p> | <p>Model #: ELB/LED-LF-48-30-830-WL4-MV ELB/LED-LF-48-30-835-WL4-MV ELB/LED-LF-48-30-840-WL4-MV ELB/LED-LF-48-30-850-WL4-MV</p> <p>Performance: Lumens = 3289 lm @ 3000k Lumens = 3340 lm @ 3000k Lumens = 3460 lm @ 3000k Lumens = 3520 lm @ 5000k</p> <p>Wattage = 28.7W > 114.5 lm/W 120 – 277VAC</p> |
|---|--|--|

All models with Power Factor > 0.99: CRI 84.9

Specification Features:

Design:

- Fixtures can be installed as suspended, ceiling mount or wall mount
- High Efficient LED's
- DLC qualified fixture
- Projected Life 55,000Hrs.
- Operates on 120-277VAC

Construction:

- Premium extruded aluminum housing
- Linear length 4'
- Finish is brushed aluminum / smooth
- Meets safety certification (UL /ETL)

Mounting:

- Suspended
- Pendant with adjustable single cable and circular canopy (sold Separately)

Controls:

- Optional dimming driver (0-10VDC)

Warranty

- 5 year warranty